




THREADED OLET

REDUCING AND FULL SIZES



REDUCING SIZES

OUTLET SIZE INCHES	DIMENSIONS			APPROX. WEIGHT POUNDS
	A	C	F	
3000 #				
1/8	3/4	5/8	7/8	.10
1/4	3/4	5/8	7/8	.10
3/8	13/16	3/4	1	.20
1/2	1	15/16	1 1/4	.24
3/4	1 1/16	1 3/16	1 7/16	.35
1	1 3/16	1 1/16	1 13/16	.62
1 1/4	1 5/16	1 3/4	2 3/16	.90
1 1/2	1 3/8	2	2 7/16	1.00
2	1 1/2	2 9/16	2 15/16	1.75
2 1/2	1 13/16	3	3 7/16	3.00
3	2	3 11/16	4 1/8	4.35
3 1/2	2 1/8	4	4 13/16	5.75
4	2 1/4	4 3/4	5 1/8	7.10
** 5	2 5/8	5 9/16	6 5/16	12.00
** 6	2 11/16	6 1/16	7 7/16	15.30
6000 #				
1/4	1 1/8	9/16	1 1/4	.30
3/8	1 1/8	9/16	1 1/4	.30
1/2	1 1/4	3/4	1 9/16	.45
3/4	1 7/16	1	1 13/16	.75
1	1 9/16	1 5/16	2 1/4	1.23
1 1/4	1 9/16	1 1/2	2 9/16	1.57
1 1/2	1 11/16	1 15/16	3	1.96
2	2 1/16	2 3/4	3 5/8	5.08

FULL SIZES *

OUTLET SIZE INCHES	A	C	D	F	APPROX. WEIGHT POUNDS
3000 #					
1/2	1	15/16	5/8	1 1/4	.15
3/4	1 1/16	1 3/16	13/16	1 7/16	.25
1	1 5/16	1 7/16	1 1/16	1 13/16	.45
1 1/4	1 7/16	1 3/4	1 3/8	2 3/16	.70
1 1/2	1 3/8	2	1 5/8	2 7/16	.90
2	1 1/2	2 9/16	2 1/16	2 15/16	1.40
2 1/2	1 13/16	3	2 1/2	3 7/16	2.50
3	2	3 11/16	3 7/16	4 1/8	4.30
3 1/2	2 1/8	4 7/16	3 9/16	4 5/8	4.50
4	2 1/4	4 3/4	4 1/16	5 1/8	6.80
** 5	2 7/16	5 1/4	5 1/4	6 5/16	9.20
** 6	2 9/16	7 1/4	6 1/16	7 7/16	15.70

FOOTNOTES

Each outlet size listed is available to fit any run curvature.

RUN PIPE SIZES Outlet sizes noted above fit a number of run pipe sizes, and the fittings are marked accordingly.

SCHEDULES

**3000# fittings are for use with standard and extra strong pipe through 4" outlet size. 6000# fittings are for use with S160 and XXS pipe. 5" and 6" fittings are rated standard weight.