



manufacture: ★Carbon steel fittings in grade B available from stock. 30-inch and smaller furnished seamless unless otherwise specified. Fittings furnished beveled to ASA standards unless otherwise specified. Schedule 160 and double extra heavy fittings 1½-8 inch are available.

dimensions: All dimensions are in inches, and in accordance with ASA B16.28 where established.

pressure-temperature ratings: Identical with those of seamless pipe of the same size, thickness and material grade.

footnotes: ●Pipe schedule numbers in accordance with ASA

▲This size and thickness has no corresponding schedule number.

pipe size nominal	outside diameter O. D.	inside diameter I. D.	wall thickness T	center to center O	back to face K	pipe schedule number*	weight (approx) lb
standard							
1	1.315	1.049	.133	2	1 ⁵ / ₈	40	.6
1¼	1.660	1.380	.140	2½	2 ¹ / ₆	40	.8
1½	1.900	1.610	.145	3	2 ¹ / ₆	40	1.3
2	2.375	2.067	.154	4	3 ³ / ₁₆	40	2.1
2½	2.875	2.469	.203	5	3 ¹⁵ / ₁₆	40	4.3
3	3.500	3.068	.216	6	4 ³ / ₄	40	6.5
3½	4.000	3.548	.226	7	5½	40	8.6
4	4.500	4.026	.237	8	6¼	40	12.8
5	5.563	5.047	.258	10	7¾	40	23.1
6	6.625	6.065	.280	12	9 ⁵ / ₁₆	40	34
8	8.625	7.981	.322	16	12 ³ / ₁₆	40	65.1
10	10.750	10.020	.365	20	15 ³ / ₈	40	120
12	12.750	12.000	.375	24	18 ³ / ₈	▲	170
14	14.000	13.250	.375	28	21	30	214
16	16.000	15.250	.375	32	24	30	276
18	18.000	17.250	.375	36	27	▲	342
20	20.000	19.250	.375	40	30	20	424
24	24.000	23.250	.375	48	36	20	612
30	30.000	29.250	.375	60	45	▲	960
36	36.000	35.250	.375	72	54	▲	1390

nominal pipe size	outside diameter O. D.	inside diameter I. D.	wall thickness T	center to center O	back to face K	pipe schedule number*	weight (approx) lb
-------------------	------------------------	-----------------------	------------------	--------------------	----------------	-----------------------	--------------------

extra strong

1	1.315	2	1 ⁵ / ₈
1¼	1.660	2½	2 ¹ / ₆
1½	1.900	1.500	.200	3	2 ¹ / ₆	80	1.4
2	2.375	1.939	.218	4	3 ³ / ₁₆	80	3.0
2½	2.875	2.323	.276	5	3 ¹⁵ / ₁₆	80	4.1
3	3.500	2.900	.300	6	4 ³ / ₄	80	8.9
3½	4.000	3.364	.318	7	5½	80	11.7
4	4.500	3.826	.337	8	6¼	80	16.6
5	5.563	4.813	.375	10	7¾	80	27.7
6	6.625	5.761	.432	12	9 ⁵ / ₁₆	80	45.7
8	8.625	7.625	.500	16	12 ³ / ₁₆	80	92
10	10.750	9.750	.500	20	15 ³ / ₈	60	147
12	12.750	11.750	.500	24	18 ³ / ₈	▲	210
14	14.000	13.000	.500	28	21	▲	217
16	16.000	15.000	.500	32	24	40	355
18	18.000	17.000	.500	36	27	▲	451
20	20.000	19.000	.500	40	30	30	560
24	24.000	23.000	.500	48	36	▲	810
30	30.000	29.000	.500	60	45	20	1272
36	36.000	35.000	.500	72	54	▲	1840