




SOCKETWELD OLET



REDUCING SIZES

OUTLET SIZE		DIMENSIONS								APPROX. WEIGHT POUNDS
INCHES	A	C	D	E	F	G	H	I		
3000 #										
1/8	3/4	5/8	.269	.420	7/8	3/8	7/32	9/32	.10	
1/4	3/4	5/8	.364	.555	7/8	3/8	7/32	9/32	.10	
3/8	13/16	3/4	.493	.690	1	3/8	7/32	7/16	.19	
1/2	1	15/16	.622	.855	1 1/4	7/16	13/64	9/16	.30	
3/4	1 1/16	1 3/16	.824	1.065	1 7/16	1/2	3/16	9/16	.34	
1	1 5/16	1 7/16	1.049	1.330	1 13/16	1 1/32	1/4	25/32	.60	
1 1/4	1 9/16	1 3/4	1.380	1.675	2 3/16	19/32	1/4	3/4	.85	
1 1/2	1 3/8	2	1.610	1.915	2 7/16	5/8	15/64	3/4	1.04	
2	1 1/2	2 9/16	2.067	2.406	2 15/16	1 1/16	1 7/64	1 1/16	1.60	
2 1/2	1 9/16	3	2.469	2.906	3 7/16	1 3/16	1 7/64	3/4	2.75	
3	1 3/4	3 11/16	3.068	3.535	4 1/8	1 3/16	1 9/64	1 9/16	3.80	
3 1/2	2 1/8	4	3.548	4.040	4 1 3/16	1 1/8	1 9/64	1	4.30	
4	1 7/8	4 3/4	4.026	4.545	5 1/8	1 3/16	1 9/64	1 1/16	7.25	
**5	2 5/8	5 9/16	5.047	5.619	6 5/16	1 9/32	1 11/32	1 11/32	12.00	
**6	2 1 1/16	6 1 1/16	6.065	6.691	7 3/8	1 9/32	1 11/32	1 13/32	14.50	
6000 #										
1/2	1 1/4	3/4	.466	.855	1 9/16	3/8	23/64	7/8	.50	
3/4	1 7/16	1	.614	1.065	1 25/32	9/16	23/64	7/8	.80	
1	1 9/16	1 1/16	.815	1.330	2 1/4	5/8	15/32	1 5/16	1.30	
1 1/4	1 5/8	1 1/2	1.160	1.675	2 9/16	1 3/16	29/64	1 3/16	1.60	
1 1/2	1 11/16	1 11/16	1.338	1.915	3	1 1/16	41/64	7/8	2.00	
2	2 1/16	2 3/4	1.689	2.406	3 5/8	7/8	39/64	1 3/16	5.13	

FULL SIZES *

OUTLET SIZE		DIMENSIONS								APPROX. WEIGHT POUNDS
INCHES	A	C	D	E	F	G	H	I		
3000 #										
1/2	1	1 5/16	.622	.855	1 1/4	15/32	13/64	1 7/32	.14	
3/4	1 1/16	1 3/16	.824	1.065	1 7/16	1 9/32	7/16	1 15/32	.25	
1	1 5/16	1 7/16	1.049	1.330	1 13/16	1 1/32	1/4	2 7/32	.44	
1 1/4	1 9/16	1 3/4	1.380	1.675	2 3/16	3/4	1/4	9/16	.64	
1 1/2	1 3/8	2	1.610	1.915	2 7/16	23/32	15/64	2 1/32	.85	
2	1 1/2	2 9/16	2.067	2.406	2 15/16	9/16	1 7/64	1 5/16	1.37	
2 1/2	1 9/16	3	2.469	2.906	3 7/16	1 3/16	1 7/64	3/4	2.25	
3	1 3/4	3 11/16	3.068	3.535	4 1/8	1 3/16	1 9/64	1 5/16	3.75	
3 1/2	1 11/16	4 7/16	3.548	4.040	4 3/4	1	1 9/64	1 1/16	4.30	
4	1 7/8	4 3/4	4.026	4.545	5 1/8	1 3/16	1 9/64	1 1/16	6.60	
**5	2 7/16	5 1/4	5.047	5.619	6 5/16	1 7/16	1 11/32	1	9.00	
**6	2 9/16	6 1 1/16	6.065	6.691	7 1/2	1 17/32	1 11/32	1 1/32	15.50	

FOOTNOTES

Each outlet size listed is available to fit any run curvature.

RUN PIPE SIZES

Outlet sizes noted above fit a number of run pipe sizes, and the fittings are marked accordingly.

SCHEDULES

**3000# fittings are for use with standard and extra strong pipe through 4" outlet size. 6000# fittings are for use with S160 and XXS pipe. 5" and 6" fittings are rated standard weight.